

SPOTLIGHT LIDER G 930 20W 15° WHITE PREMIUM COLOR ON/OFF

Article number: N008-K0003-PC930-HA-M15-ZE53_500-S2-###





COB

3000 [K] PREMIUM COLOR Light colour

CRI

90 Led chip flux 2200 [lm] Luminous flux 1980 [lm] System power 20 [W] Luminaire Efficiency 99 [lm/W] Beam angle 15° Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 0,69 [kg] Protection rating IP, IK, class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska