

## SPOTLIGHT LIDER G 827 19W 15° WHITE | ON/OFF

Article number: N008-K0003-RF827-H5-M15-ZE53\_500-S2-###





COB Light colour 2700 [K] | CRI 2694 [lm] Led chip flux Luminous flux 2424 [lm] System power 19 [W] Luminaire Efficiency 128 [lm/W] Beam angle 15° Controller ON/OFF MacAdam 3 SDCM

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

## LUMINAIRE

Weight 0,69 [kg]

Protection rating IP, IK, class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 22.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska