

# SPOTLIGHT LIDER G 830 14W 38° WHITE | ON/OFF

Article number: N008-K0003-RF830-H5-M38-ZE53\_350-S2-###



LED	COB
Light colour	3000 [K]
CRI	80
Led chip flux	1905 [lm]
Luminous flux	1714 [lm]
System power	14 [W]
Luminaire Efficiency	122 [lm/W]
Beam angle	38°
Controller	ON/OFF
MacAdam	3 SDCM

### Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

### LUMINAIRE

Weight	0.69 [kg]
Protection rating IP , IK , class	IP 20, IK 01,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10%  
System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 22.09.2024



+48 32 388 80 00



www.cora.pl

cora@cora.pl



Street: Ignatza Hakuby 18

41-914 Bytom, Polska