

SPOTLIGHT

SPOTLIGHT LIDER G 840 21W 15° WHITE | ON/OFF

Article number: N008-K0003-RF840-H5-M15-ZE53_550-S2-###



COB



UMINAIRE		
MacAdam	3 SDCM	
Controller	ON/OFF	
Beam angle	15°	
Luminaire Efficiency	134 [lm/W]	
System power	21 [W]	
Luminous flux	2809 [lm]	
Led chip flux	3122 [lm]	
CRI	80	black an available
Light colour	4000 [K]	Compac

Spotlight LED

ct track mounted LED spotlight. Aluminium housing. Available in white, and grey. Any RAL palette colour available on enquiry. Reflector beams ale: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LU

0,69 [kg]
IP 20, IK 1,
WHITE
Plastic
220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska