

## SPOTLIGHT

## SPOTLIGHT LIDER G 850 10W 23° WHITE | ON/OFF

Article number: N008-K0003-RF850-H5-M23-ZE63\_250-S2-###



COB

80 1447 [lm]

5000 [K] |

1302 [lm]

130 [lm/W]

ON/OFF

3 SDCM

10 [W]

23°



| -        |      |     |    |    |
|----------|------|-----|----|----|
| <u> </u> | noti | lia | ht |    |
| - 0      | ρυι  | пy  | ш. | ᇆᄓ |

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

| т | ш | N | u | N | Δ | IR | F |
|---|---|---|---|---|---|----|---|

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

| JMINAINE                          |                  |  |  |  |  |
|-----------------------------------|------------------|--|--|--|--|
| Weight                            | 0,69 [kg]        |  |  |  |  |
| Protection rating IP , IK , class | IP 20, IK 1,     |  |  |  |  |
| Luminaire colour                  | WHITE            |  |  |  |  |
| Cover                             | Plastic          |  |  |  |  |
| Operating voltage                 | 220-240V 50-60Hz |  |  |  |  |
|                                   |                  |  |  |  |  |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024