

## SPOTLIGHT

## SPOTLIGHT LIDER G 850 19W 38° WHITE | ON/OFF

Article number: N008-K0003-RF850-H5-M38-ZE53\_500-S2-###



COB

80 2895 [lm]

5000 [K] |

2605 [lm]

137 [lm/W]

ON/OFF

3 SDCM

19 [W]

38°



<b>c</b>	. <b>at</b> l	licel	h+			n
ວບ	οι	IU	ш	_		U
		- 3			_	

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

т	ш	N	u	N	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE					
Weight	0,69 [kg]				
Protection rating IP , IK , class	IP 20, IK 1,				
Luminaire colour	WHITE				
Cover	Plastic				
Operating voltage	220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024