

SPOTLIGHT

SPOTLIGHT LIDER G 930 14W 15° WHITE | ON/OFF

Article number: N008-K0003-RF930-H5-M15-ZE53_350-S2-###



COB



MacAdam	3 SDCM	_
Controller	ON/OFF	
Beam angle	15°	
Luminaire Efficiency	104 [lm/W]	
System power	14 [W]	
Luminous flux	1451 [lm]	
Led chip flux	1613 [lm]	
CRI	90	black availa
Light colour	3000 [K]	Com

Spotlight LED

npact track mounted LED spotlight. Aluminium housing. Available in white, & and grey. Any RAL palette colour available on enquiry. Reflector beams ilable: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska