

SPOTLIGHT

SPOTLIGHT LIDER G 940 25W 45° WHITE | ON/OFF

Article number: N008-K0003-RF940-H5-M45-ZE53_650-S2-###





4000 [K]	Compa black a availab
90	
3141 [lm]	
2826 [lm]	
25 [W]	
113 [lm/W]	
45°	

ON/OFF

3 SDCM

СОВ

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Available in white, plack and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Controller

MacAdam

Light colour

CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle

Weight	0,69 [kg]	
Protection rating IP , IK , class	IP 20, IK 1,	
Luminaire colour	WHITE	
Cover	Plastic	
Operating voltage	220-240V 50-60Hz	

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024