

SPOTLIGHT

SPOTLIGHT LIDER G 825 14W 45° WHITE BREAD ON/OFF

Article number: N008-K0003-VF825-H5-M45-ZE53_350-S2-###



СОВ

80 1674 [lm]

1506 [lm]

108 [lm/W]

ON/OFF

3 SDCM

14 [W]

45°

2500 [K] BREAD



Cnot	liah	+ I C	=n
Sput	nyn		-

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

т	ш	N	u	N	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

0,69 [kg]				
IP 20, IK 1,				
WHITE				
Plastic				
220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024