

SPOTLIGHT

SPOTLIGHT LIDER G 825 21W 45° WHITE BREAD ON/OFF

Article number: N008-K0003-VF825-H5-M45-ZE53_550-S2-###



СОВ

80 2574 [lm]

2316 [lm]

110 [lm/W]

ON/OFF

3 SDCM

21 [W]

45°

2500 [K] BREAD



opolingin LLD	S	pot	ligh	t L	ED
---------------	---	-----	------	-----	----

Compact track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 25W

LUMINAIRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	0,69 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.06.2024