

## SPOTLIGHT LIDER D MICRO 930 19W 45° GREY CRI97 ON/OFF

Article number: N009-K0001-HI930-H6-C45-ZE51\_500-##-###



COB



 Light colour
 3000 [K] CRI97

 CRI
 90

 Led chip flux
 2199 [lm]

 Luminous flux
 1979 [lm]

 System power
 19 [W]

 Luminaire Efficiency
 104 [lm/W]

 Beam angle
 45°

Beam angle 45°
Controller ON/OFF
MacAdam 3 SDCM

## LUMINAIRE

Weight 0,6 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

## Spotlight LED

Track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 25° and 45°. Maximum power is 19W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska