

SPOTLIGHT

SPOTLIGHT LIDER D MICRO 825 10W 15° GREY BREAD ON/OFF

COB

80

1195 [lm]

1075 [lm]

108 [lm/W]

ON/OFF

3 SDCM

10 [W]

15°

2500 [K] BREAD

Article number: N009-K0001-VF825-H6-C15-ZE61_250-##-###



_					_
S	not	lia	ht	I FI	1
~	201		••••		1

Track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 25° and 45°. Maximum power is 19W

LU	MIN	AIF	RE

Light colour CRI

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

Weight	0,6 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

Generated: 02.06.2024