

SPOTLIGHT LIDER D MICRO 825 14W 25° WHITE BREAD ON/OFF

Article number: N009-K0003-VF825-H6-C25-ZE53_350-##-###





.ED COB

Light colour 2500 [K] BREAD

CRI 8

 Led chip flux
 1674 [Im]

 Luminous flux
 1506 [Im]

 System power
 14 [W]

 Luminaire Efficiency
 108 [Im/W]

 Beam angle
 25°

 Controller
 ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 0,6 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 25° and 45°. Maximum power is 19W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

 $\ensuremath{\mathsf{RAL}}$ colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.202



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska