

## SPOTLIGHT SNIPER F 827 27W 30° WHITE | ON/OFF

Article number: N013-K0003-RF827-H5-S30-ZA02\_700-S3-###




IP 20, IK 3,

220-240V 50-60Hz

WHITE

Glass



Light colour2700 [K]  CRI80Led chip flux3772 [lm]Luminous flux3017 [lm]System power27 [W]Luminaire Efficiency112 [lm/W]Beam angle30°ControllerON/OFFMacAdam3 SDCMLUMINAIREWeight1,47 [kg]	LED	COB	:
Led chip flux3772 [lm]Luminous flux3017 [lm]System power27 [W]Luminaire Efficiency112 [lm/W]Beam angle30°ControllerON/OFFMacAdam3 SDCM	Light colour	2700 [K]	
Luminous flux3017 [lm]System power27 [W]Luminaire Efficiency112 [lm/W]Beam angle30°ControllerON/OFFMacAdam3 SDCM	CRI	80	l
System power 27 [W]   Luminaire Efficiency 112 [lm/W]   Beam angle 30°   Controller ON/OFF   MacAdam 3 SDCM	Led chip flux	3772 [lm]	I
Luminaire Efficiency 112 [lm/W]   Beam angle 30°   Controller ON/OFF   MacAdam 3 SDCM	Luminous flux	3017 [lm]	
Beam angle 30°   Controller ON/OFF   MacAdam 3 SDCM	System power	27 [W]	
Controller ON/OFF MacAdam 3 SDCM	Luminaire Efficiency	112 [lm/W]	
MacAdam 3 SDCM	Beam angle	30°	
LUMINAIRE	Controller	ON/OFF	
	MacAdam	3 SDCM	
Weight 1,47 [kg]	LUMINAIRE		-
	Weight	1,47 [kg]	

## Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 20°, 30°, 45° and 60°. Maximum power is 30W

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024