

## SPOTLIGHT SNIPER F 930 31W 45° WHITE | ON/OFF

Article number: N013-K0003-RF930-H5-S45-ZA03\_800-S3-###




IP 20, IK 3,

220-240V 50-60Hz

WHITE

Glass



| Light colour3000 [K]  CRI90Led chip flux3688 [lm]Luminous flux2950 [lm]System power31 [W]Luminaire Efficiency95 [lm/W]Beam angle45°ControllerON/OFFMacAdam3 SDCMLUMINAIREWeight1,47 [kg] |           | LED                  | COB       |
|--|-----------|----------------------|-----------|
| Led chip flux3688 [lm]Luminous flux2950 [lm]System power31 [W]Luminaire Efficiency95 [lm/W]Beam angle45°ControllerON/OFFMacAdam3 SDCM  |           | Light colour         | 3000 [K]  |
| Luminous flux2950 [lm]System power31 [W]Luminaire Efficiency95 [lm/W]Beam angle45°ControllerON/OFFMacAdam3 SDCM  |           | CRI                  | 90        |
| System power 31 [W]   Luminaire Efficiency 95 [Im/W]   Beam angle 45°   Controller ON/OFF   MacAdam 3 SDCM   |           | Led chip flux        | 3688 [lm] |
| Luminaire Efficiency 95 [Im/W]   Beam angle 45°   Controller ON/OFF   MacAdam 3 SDCM   |           | Luminous flux        | 2950 [lm] |
| Beam angle 45°<br>Controller ON/OFF<br>MacAdam 3 SDCM  |           | System power         | 31 [W]    |
| Controller ON/OFF<br>MacAdam 3 SDCM  |           | Luminaire Efficiency | 95 [lm/W] |
| MacAdam 3 SDCM   |           | Beam angle           | 45°       |
| LUMINAIRE  |           | Controller           | ON/OFF    |
|  |           | MacAdam              | 3 SDCM    |
|  | -         |                      |           |
| Weight 1,47 [kg]   | LUMINAIRE |                      |           |
|  |           | Weight               | 1,47 [kg] |

## Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 20°, 30°, 45° and 60°. Maximum power is 30W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 28.06.2024