

SPOTLIGHT

SPOTLIGHT SNIPER G MAXI 827 23W 15° WHITE | ON/OFF

Article number: N014-K0003-RF827-H5-S15-ZA02_600-S3-###



IP 20, IK 1,

220-240V 50-60Hz

WHITE

Glass



Light colour2700 [K] CRI80Led chip flux3233 [lm]Luminous flux2586 [lm]System power23 [W]Luminaire Efficiency112 [lm/W]Beam angle15°ControllerON/OFFMacAdam3 SDCMUMINAIREWeight1,02 [kg]	L	ED	COB
Led chip flux3233 [lm]Luminous flux2586 [lm]System power23 [W]Luminaire Efficiency112 [lm/W]Beam angle15°ControllerON/OFFMacAdam3 SDCM	Li	ight colour	2700 [K]
Luminous flux2586 [lm]System power23 [W]Luminaire Efficiency112 [lm/W]Beam angle15°ControllerON/OFFMacAdam3 SDCM	С	RI	80
System power 23 [W] Luminaire Efficiency 112 [Im/W] Beam angle 15° Controller ON/OFF MacAdam 3 SDCM	L	ed chip flux	3233 [lm]
Luminaire Efficiency 112 [lm/W] Beam angle 15° Controller ON/OFF MacAdam 3 SDCM	L	uminous flux	2586 [lm]
Beam angle 15° Controller ON/OFF MacAdam 3 SDCM	S	ystem power	23 [W]
Controller ON/OFF MacAdam 3 SDCM	L	uminaire Efficiency	112 [lm/W]
MacAdam 3 SDCM	В	eam angle	15°
UMINAIRE	С	ontroller	ON/OFF
	M	lacAdam	3 SDCM
Weight 1,02 [kg]	UMINAIRE		
	W	/eight	1,02 [kg]

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 20°, 30°, 45° and 60°. Maximum power is 30W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

L

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024