

## SPOTLIGHT SNIPER G MAXI 830 25W 20° WHITE | ON/OFF

Article number: N014-K0003-RF830-H5-S20-ZA02\_650-S3-###



IP 20, IK 1,

220-240V 50-60Hz

WHITE

Glass



Light colour3000 [K]  CRI80Led chip flux3538 [lm]Luminous flux2830 [lm]System power25 [W]Luminaire Efficiency113 [lm/W]Beam angle20°ControllerON/OFFMacAdam3 SDCMLUMINAIREWeight1,02 [kg]		LED	СОВ
Led chip flux3538 [lm]Luminous flux2830 [lm]System power25 [W]Luminaire Efficiency113 [lm/W]Beam angle20°ControllerON/OFFMacAdam3 SDCM		Light colour	3000 [K]
Luminous flux2830 [lm]System power25 [W]Luminaire Efficiency113 [lm/W]Beam angle20°ControllerON/OFFMacAdam3 SDCM		CRI	80
System power 25 [W]   Luminaire Efficiency 113 [Im/W]   Beam angle 20°   Controller ON/OFF   MacAdam 3 SDCM		Led chip flux	3538 [lm]
Luminaire Efficiency 113 [lm/W]   Beam angle 20°   Controller ON/OFF   MacAdam 3 SDCM		Luminous flux	2830 [lm]
Beam angle 20° Controller ON/OFF MacAdam 3 SDCM		System power	25 [W]
Controller ON/OFF MacAdam 3 SDCM		Luminaire Efficiency	113 [lm/W]
MacAdam 3 SDCM		Beam angle	20°
UMINAIRE		Controller	ON/OFF
		MacAdam	3 SDCM
Weight 1,02 [kg]	UMINAIRE		
		Weight	1,02 [kg]

## Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 20°, 30°, 45° and 60°. Maximum power is 30W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

Cover

L

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 23.06.2024