

## SPOTLIGHT SNIPER D MINI 930 14W 24° WHITE PREMIUM WHITE ON/OFF

Article number: N016-K0003-HE930-HA-D24-ZA01\_350-S5-###



Light colour3000 [K] PREMIUM WHITECRI90Led chip flux2064 [Im]Luminous flux1651 [Im]System power14 [W]Luminaire Efficiency118 [Im/W]Beam angle24°ControllerON/OFFMacAdam3 SDCM	LED	СОВ
CRI90Led chip flux2064 [lm]Luminous flux1651 [lm]System power14 [W]Luminaire Efficiency118 [lm/W]Beam angle24°ControllerON/OFF	Light colour	
Led chip flux2064 [lm]Luminous flux1651 [lm]System power14 [W]Luminaire Efficiency118 [lm/W]Beam angle24°ControllerON/OFFMacAdamON/OFF	CRI	
Luminous flux1651System power1651Luminaire Efficiency14 [W]Beam angle24°ControllerON/OFF	Led chip flux	90
1651 [lm]   System power   Luminaire Efficiency   Beam angle   Controller   MacAdam	Luminous flux	2064 [lm]
14 [W]   Luminaire Efficiency   118 [Im/W]   Beam angle   Controller   MacAdam		1651 [lm]
Luminaire Efficiency 118 [Im/W] Beam angle 24° Controller ON/OFF MacAdam	System power	14 [W]
Beam angle 24° Controller ON/OFF	Luminaire Efficiency	
Controller ON/OFF MacAdam	Beam angle	1 18 [im/vv]
ON/OFF MacAdam	Controller	24°
		ON/OFF
	MacAdam	3 SDCM

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 24°, 38° and 60°. Maximum power is 21W

## LUMINAIRE

Weight	1 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.05.2024