

## SPOTLIGHT LIDER GLS 930 14W 45° WHITE CRI97 ON/OFF

Article number: N033-K0003-HI930-H5-G45-ZE53\_350-S2-###



.ED COB

Light colour 3000 [K] CRI97

CRI 90

 Led chip flux
 1575 [lm]

 Luminous flux
 1512 [lm]

 System power
 14 [W]

 Luminaire Efficiency
 108 [lm/W]

 Beam angle
 45°

 Controller
 ON/OFF

Controller ON/OFF
MacAdam 3 SDCM

## LUMINAIRE

 Weight
 0,7 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 WHITE

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 24°, 38° and 60°. Maximum power is 31W

Note: All data are typical values. Tolerance of measurements  $\pm 1.10\%$  System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry,



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska