

SPOTLIGHT

SPOTLIGHT LIDER D MINI 935 27W 23° BLACK HI EFFICIENT ON/OFF

Article number: N035-K0002-BB935-H5-M23-ZE52_700-S2-###





Light colour3500 [K] HI EFFICIENTCRI90Led chip flux4181 [Im]Luminous flux3762 [Im]System power27 [W]Luminaire Efficiency139 [Im/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	LED	СОВ
CRI90Led chip flux4181 [lm]Luminous flux3762 [lm]System power27 [W]Luminaire Efficiency139 [lm/W]Beam angle23°ControllerON/OFF	Light colour	
Led chip flux4181 [lm]Luminous flux3762 [lm]System power27 [W]Luminaire Efficiency139 [lm/W]Beam angle23°ControllerON/OFF	CRI	
Luminous flux3762 [Im]System power27 [W]Luminaire Efficiency139 [Im/W]Beam angle23°ControllerON/OFF	Led chip flux	
System power27 [W]Luminaire Efficiency139 [Im/W]Beam angle23°ControllerON/OFF	Luminous flux	4181 [lm]
27 [W] Luminaire Efficiency 139 [Im/W] Beam angle 23° Controller ON/OFF	Sustam nowor	3762 [lm]
139 [Im/W] Beam angle Controller MacAdam	System power	27 [W]
Beam angle 23° Controller ON/OFF	Luminaire Efficiency	139 [lm/\/]
Controller ON/OFF MacAdam	Beam angle	
MacAdam	Controller	23°
	MasAdam	ON/OFF
	WacAdam	3 SDCM

Spotlight LED

Track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 35W.

LUMINAIRE

Weight	0,7 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024