

SPOTLIGHT LIDER D MINI 835 10W 15° BLACK | ON/OFF

Article number: N035-K0002-RF835-H5-M15-ZE62_250-S2-###



IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic



LED	COB	Spo
Light colour	3500 [K]	Trac poss on e pow
CRI	80	
Led chip flux	1391 [lm]	
Luminous flux	1251 [lm]	
System power	10 [W]	
Luminaire Efficiency	125 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 35W..

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024