

SPOTLIGHT LIDER D MINI 930 23W 60° BLACK | ON/OFF

Article number: N035-K0002-RF930-H5-M60-ZE52_600-S2-###





LED	COB	Spotlig
Light colour	3000 [K]	Track m possible on enqu power is
CRI	90	
Led chip flux	2767 [lm]	
Luminous flux	2490 [lm]	
System power	23 [W]	
Luminaire Efficiency	108 [lm/W]	
Beam angle	60°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		_
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

Spotlight LED

Frack mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 35W..

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

Operating voltage

Luminaire colour

Protection rating IP , IK , class

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024