

SPOTLIGHT LIDER D MINI 940 21W 15° BLACK | ON/OFF

Article number: N035-K0002-RF940-H5-M15-ZE52_550-S2-###





LED	COB	Spotlight L
Light colour	4000 [K]	Track moun possible. Av on enquiry. power is 35
CRI	90	
Led chip flux	2658 [lm]	
Luminous flux	2392 [lm]	
System power	21 [W]	
Luminaire Efficiency	114 [lm/W]	
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic

LED

nted LED spotlight. Aluminium housing. Ceiling base installation Available in white, black and grey. Any RAL palette colour available r. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum 5W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska