

SPOTLIGHT LIDER D MINI 825 19W 45° BLACK BREAD ON/OFF

Article number: N035-K0002-VF825-H5-M45-ZE52_500-S2-###



IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic



LED	COB	Spotlig
Light colour	2500 [K] BREAD	Track n possibl on enq power i
CRI	80	
Led chip flux	2340 [lm]	
Luminous flux	2106 [lm]	
System power	19 [W]	
Luminaire Efficiency	111 [lm/W]	
Beam angle	45°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	0,7 [kg]	

Spotlight LED

rack mounted LED spotlight. Aluminium housing. Ceiling base installation ossible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum ower is 35W..

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024