

SPOTLIGHT LIDER D MINI 957 10W 23° WHITE SPECIAL ON/OFF

Article number: N035-K0003-CC957-H5-M23-ZE63_250-S2-###



IP 20, IK 1,

220-240V 50-60Hz

WHITE

Plastic



CRI 90 poss on er	LED	COB	Spotli
CRI90Led chip flux1318 [lm]Luminous flux1186 [lm]System power10 [W]Luminaire Efficiency119 [lm/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	Light colour	5700 [K] SPECIAL	Track r possibi on enq power
Led chip flux1318 [m]Luminous flux1186 [m]System power10 [W]Luminaire Efficiency119 [lm/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	CRI	90	
System power10 [W]Luminaire Efficiency119 [Im/W]Beam angle23°ControllerON/OFFMacAdam3 SDCM	Led chip flux	1318 [lm]	
Luminaire Efficiency 119 [lm/W] Beam angle 23° Controller ON/OFF MacAdam 3 SDCM	Luminous flux	1186 [lm]	
Beam angle 23° Controller ON/OFF MacAdam 3 SDCM	System power	10 [W]	
Controller ON/OFF MacAdam 3 SDCM	Luminaire Efficiency	119 [lm/W]	
MacAdam 3 SDCM	Beam angle	23°	
LUMINAIRE	Controller	ON/OFF	
	MacAdam	3 SDCM	
Weight 0,7 [kg]	LUMINAIRE		
	Weight	0,7 [kg]	

Spotlight LED

rack mounted LED spotlight. Aluminium housing. Ceiling base installation ossible. Available in white, black and grey. Any RAL palette colour available in enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum ower is 35W..

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024