


SPOTLIGHT LIDER A MINI 840 21W 60° BLACK | ON/OFF

Article number: N036-K0002-RF840-H5-M60-ZE52_550-S2-###



LED	COB
Light colour	4000 [K]
CRI	80
Led chip flux	3122 [lm]
Luminous flux	2809 [lm]
System power	21 [W]
Luminaire Efficiency	134 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

LUMINAIRE

Weight	0,55 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska