

## SPOTLIGHT

# SPOTLIGHT LIDER A MINI 935 19W 60° WHITE HI EFFICIENT ON/OFF

Article number: N036-K0003-BB935-H5-M60-ZE53\_500-S2-###



UMINAIRE			
	wab dam	3 SDCM	
	MacAdam	ON/OFF	
	Controller	60°	
	Beam angle	145 [lm/W]	
	Luminaire Efficiency	19 [W]	
	System power	2748 [lm]	
	Luminous flux	3054 [lm]	
	Led chip flux	90	
	CRI	EFFICIENT	
	Light colour	3500 [K] HI	
	LED	СОВ	

# Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

#### LU MINAIRE

Weight	0,55 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

### Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska