

SPOTLIGHT LIDER A MINI 935 10W 60° WHITE HI EFFICIENT ON/OFF

Article number: N036-K0003-BB935-H5-M60-ZE63_250-S2-###



| | |
|----------------------|-----------------------|
| LED | COB |
| Light colour | 3500 [K] HI EFFICIENT |
| CRI | 90 |
| Led chip flux | 1571 [lm] |
| Luminous flux | 1413 [lm] |
| System power | 10 [W] |
| Luminaire Efficiency | 141 [lm/W] |
| Beam angle | 60° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

LUMINAIRE

| | |
|-----------------------------------|------------------|
| Weight | 0,55 [kg] |
| Protection rating IP , IK , class | IP 20, IK 1, |
| Luminaire colour | WHITE |
| Cover | Plastic |
| Operating voltage | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska