

## SPOTLIGHT LIDER A MINI 930 10W 60° WHITE | ON/OFF

Article number: N036-K0003-RF930-H5-M60-ZE63\_250-S2-###





LED	COB
Light colour	3000 [K]
CRI	90
Led chip flux	1152 [lm]
Luminous flux	1036 [lm]
System power	10 [W]
Luminaire Efficiency	104 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

## Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

## LUMINAIRE

Weight 0,55 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska