

SPOTLIGHT LIDER A MINI 825 25W 23° WHITE BREAD ON/OFF

Article number: N036-K0003-VF825-H5-M23-ZE53_650-S2-###



COB



 Light colour
 2500 [K] BREAD

 CRI
 80

 Led chip flux
 3042 [lm]

 Led chip flux
 3042 [Im]

 Luminous flux
 2737 [Im]

 System power
 25 [W]

 Luminaire Efficiency
 109 [Im/W]

 Beam angle
 23°

 Controller
 ON/OFF

 MacAdam
 3 SDCM

LUMINAIRE

Weight 0,55 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Spotlight LED

Compact track mounted LED spotlight. Aluminium housing. Ceiling base installation possible. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 23°, 38°, 45° and 60°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska