

DOWNLIGHT LIDER N 830 25W 60° GREY | ON/OFF

Article number: N201-K0001-RF830-H5-G60-ZA02_650-S1-###



195 mm



∅ 107 mm

LED	COB
Light colour	3000 [K]
CRI	80
Led chip flux	3538 [lm]
Luminous flux	3184 [lm]
System power	25 [W]
Luminaire Efficiency	127 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

Surface mounted LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight	0,96 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

kolor oprawy do wyboru z palety RAL - na zapytanie, możliwość sterowania mocą świecenia za pomocą systemu CASAMBI / DALI / PHASE CUT



Generated: 29.06.2024



+48 32 388 80 00



www.corra.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska