

DOWNLIGHT LIDER N 930 25W 15° BLACK | ON/OFF

Article number: N201-K0002-RF930-H5-G15-ZA02_650-S1-###



LED	COB
Light colour	3000 [K]
CRI	90
Led chip flux	2997 [lm]
Luminous flux	2697 [lm]
System power	25 [W]
Luminaire Efficiency	108 [lm/W]
Beam angle	15°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

Surface mounted LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight	0.66 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10%
System features may change with product improvements due to technical advances.

OPTIONS

kolor oprawy do wyboru z palety RAL - na zapytanie,
możliwość sterowania mocą świecenia za pomocą systemu
CASAMBI / DALI / PHASE CUT



Generated: 27.09.2024



+48 32 388 80 00



www.cora.pl

cora@cora.pl



Street: Ignatza Hakuby 18

41-914 Bytom, Polska