

## DOWNLIGHT LIDER N 957 10W 38° WHITE SPECIAL ON/OFF

Article number: N201-K0003-CC957-H5-G38-ZA01\_250-S1-###



195 mm



∅ 107 mm

LED	COB
Light colour	5700 [K] SPECIAL
CRI	90
Led chip flux	1318 [lm]
Luminous flux	1186 [lm]
System power	10 [W]
Luminaire Efficiency	119 [lm/W]
Beam angle	38°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

Surface mounted LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° 45° and 60°. Maximum power is 31W.

### LUMINAIRE

Weight	0,96 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

kolor oprawy do wyboru z palety RAL - na zapytanie, możliwość sterowania mocą świecenia za pomocą systemu CASAMBI / DALI / PHASE CUT



Generated: 16.07.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska