

DOWNLIGHT LIDER N 930 25W 15° WHITE PREMIUM COLOR ON/OFF

Article number: N201-K0003-PC930-HA-G15-ZA02_650-S1-###



LED	COB
Light colour	3000 [K] PREMIUM COLOR
CRI	
Led chip flux	90
Luminous flux	2776 [lm]
System power	2498 [lm]
Luminaire Efficiency	25 [W]
Beam angle	100 [lm/W]
Controller	15°
MacAdam	ON/OFF 3 SDCM

Downlight LED

Surface mounted LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° 45° and 60°. Maximum power is 31W.

LUMINAIRE

Weight	0.66 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10%. System features may change with product improvements due to technical advances.

OPTIONS

kolor oprawy do wyboru z palety RAL - na zapytanie,
możliwość sterowania mocą świecenia za pomocą systemu
CASAMBI / DALI / PHASE CUT





+48 32 388 80 00



www.cora.pl

cora@cora.pl



Street: Ignatza Hakuby 18

41-914 Bytom, Polska