

## DOWNLIGHT LIDER N 840 19W 60° WHITE | ON/OFF

Article number: N201-K0003-RF840-H5-G60-ZA01\_500-S1-###



195 mm



Ø 107 mm

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | 4000 [K]   |
| CRI                  | 80         |
| Led chip flux        | 2839 [lm]  |
| Luminous flux        | 2555 [lm]  |
| System power         | 19 [W]     |
| Luminaire Efficiency | 134 [lm/W] |
| Beam angle           | 60°        |
| Controller           | ON/OFF     |
| MacAdam              | 3 SDCM     |

### Downlight LED

Surface mounted LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° 45° and 60°. Maximum power is 31W.

### LUMINAIRE

|                                   |                  |
|-----------------------------------|------------------|
| Weight                            | 0,96 [kg]        |
| Protection rating IP , IK , class | IP 20, IK 1,     |
| Luminaire colour                  | WHITE            |
| Cover                             | Plastic          |
| Operating voltage                 | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

kolor oprawy do wyboru z palety RAL - na zapytanie, możliwość sterowania mocą świecenia za pomocą systemu CASAMBI / DALI / PHASE CUT



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska