

## DOWNLIGHT LIDER Z 940 23W 45° GREY HI EFFICIENT ON/OFF

Article number: N202-K0001-BB940-H5-G45-ZA02\_600-S1-###



COB

90

4000 [K] HI EFFICIENT

3793 [lm]

3413 [lm]


148 [lm/W]

ON/OFF

3 SDCM

23 [W]

45°



Down	lia	ht	
DOWIN	ny	ш.	ᄕ

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

I I IMAINIAIDE	
LUMINAINE	-

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE	
Weight	1,17 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska