

DOWNLIGHT LIDER Z 957 10W 45° GREY SPECIAL ON/OFF

Article number: N202-K0001-CC957-H5-G45-ZA01_250-S1-###



СОВ

90 1318 [lm]

1186 [lm]


10 [W] 119 [lm/W]

45°

ON/OFF

3 SDCM

5700 [K] SPECIAL



Down	lia	ht	
DOWIN	ny	ш.	ᄕ

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

11	111	Л	N.	ΔI	R	F.

Controller

MacAdam

Light colour

Led chip flux Luminous flux

System power

Luminaire Efficiency Beam angle

CRI

JMINAIRE				
Weight	1,17 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	GREY			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024