


DOWNLIGHT LIDER Z 930 25W 15° GREY PREMIUM WHITE ON/OFF

Article number: N202-K0001-HE930-HA-G15-ZA02_650-S1-###





_ED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 3659 [lm]

 Luminous flux
 3293 [lm]

 System power
 25 [W]

 Luminaire Efficiency

Beam angle 132 [lm/W]

Controller

MacAdam

3 SDCM

LUMINAIRE

Weight 1,17 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.

+48 32 388 80 00



Generated: 02.06.202



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska