


## DOWNLIGHT LIDER Z 830 21W 15° GREY | ON/OFF

Article number: N202-K0001-RF830-H5-G15-ZA02\_550-S1-###





COB Light colour 3000 [K] | CRI 2994 [lm] Led chip flux Luminous flux 2694 [lm] System power 21 [W] Luminaire Efficiency 128 [lm/W] Beam angle 15° Controller ON/OFF MacAdam 3 SDCM

## Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

## LUMINAIRE

Weight 1,17 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour GREY

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska