

DOWNLIGHT LIDER Z 830 25W 23° GREY | ON/OFF

Article number: N202-K0001-RF830-H5-G23-ZA02_650-S1-###



COB

80 3538 [lm]

3000 [K] |

3184 [lm]


127 [lm/W]

ON/OFF

3 SDCM

25 [W]

23°



Downlinkt I CD			
	Down	liah	
Downliant LED		nan	

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

н	ш	IN/	IN	Δ	IR	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE			
Weight	1,17 [kg]		
Protection rating IP , IK , class	IP 20, IK 1,		
Luminaire colour	GREY		
Cover	Plastic		
Operating voltage	220-240V 50-60Hz		

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska