

DOWNLIGHT LIDER Z 840 25W 23° GREY | ON/OFF

Article number: N202-K0001-RF840-H5-G23-ZA02_650-S1-###



COB

80 3690 [lm]

4000 [K] |

3321 [lm]


133 [lm/W]

ON/OFF

3 SDCM

25 [W]

23°



Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

LUMINAIRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,17 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	GREY
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00





Street: Ignatza Hakuby 18 41-914 Bytom, Polska