

DOWNLIGHT LIDER Z 935 19W 15° BLACK HI EFFICIENT ON/OFF

Article number: N202-K0002-BB935-H5-G15-ZA01_500-S1-###



COB

90

3500 [K] HI EFFICIENT

3054 [lm]

2748 [lm]


145 [lm/W]

ON/OFF

3 SDCM

19 [W]

15°



_			
Down	lia	ht	I FD
DOWN	чy		

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

11	IM/I	INΔ	IR	F.

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE				
1,17 [kg]				
IP 20, IK 1,				
BLACK				
Plastic				
220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska