


DOWNLIGHT LIDER Z 940 31W 15° BLACK HI EFFICIENT ON/OFF

Article number: N202-K0002-BB940-H5-G15-ZA03_800-S1-###





COB 4000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 4964 [lm] Luminous flux 4467 [lm] System power 31 [W] Luminaire Efficiency 144 [lm/W] Beam angle 15° Controller ON/OFF MacAdam 3 SDCM

Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

LUMINAIRE

Weight 1,17 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour BLACK

Cover Plastic

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska