

## DOWNLIGHT LIDER Z 940 23W 23° BLACK HI EFFICIENT ON/OFF

Article number: N202-K0002-BB940-H5-G23-ZA02\_600-S1-###



COB

90

4000 [K] HI EFFICIENT

3793 [lm]

3413 [lm]


148 [lm/W]

ON/OFF

3 SDCM

23 [W]

23°



## Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

111	M	NΔ	IR	F.

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE				
Weight	1,17 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	WHITE			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl  $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 17.09.2024