

DOWNLIGHT LIDER Z 930 10W 45° BLACK CRI97 ON/OFF

Article number: N202-K0002-HI930-H5-G45-ZA01_250-S1-###



СОВ

90 1144 [lm]

1029 [lm]

103 [lm/W]


ON/OFF

3 SDCM

10 [W]

45°

3000 [K] CRI97



Downli	abt	
DOWIII	ynu	LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

11	111	Л	N.	ΔI	R	F.

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE				
Weight	1,17 [kg]			
Protection rating IP , IK , class	IP 20, IK 1,			
Luminaire colour	BLACK			
Cover	Plastic			
Operating voltage	220-240V 50-60Hz			
Cover	Plastic			

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024