

## DOWNLIGHT LIDER Z 840 10W 15° BLACK | ON/OFF

Article number: N202-K0002-RF840-H5-G15-ZA01\_250-S1-###



COB

80 1419 [lm]

4000 [K] |

1277 [lm]


128 [lm/W]

ON/OFF

3 SDCM

10 [W]

15°



Down	liak	at L	ED
DOWN	ngi		

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

11	111	Л	N.	ΔI	R	F.

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE				
1,17 [kg]				
IP 20, IK 1,				
BLACK				
Plastic				
220-240V 50-60Hz				

## Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska