

DOWNLIGHT LIDER Z 840 25W 15° BLACK | ON/OFF

Article number: N202-K0002-RF840-H5-G15-ZA02_650-S1-###




IP 20, IK 1,

220-240V 50-60Hz

BLACK

Plastic



LED	COB	Downligh
Light colour	4000 [K]	Suspende
CRI	80	Available enquiry. F and 60°. I
Led chip flux	3690 [lm] 3321 [lm] 25 [W]	
Luminous flux System power		
Beam angle	15°	
Controller	ON/OFF	
MacAdam	3 SDCM	
LUMINAIRE		
Weight	1,17 [kg]	

nlight LED

ded LED downlight. Aluminium housing. Plastic cover included. e in white, black and grey. Any RAL palette colour available on Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska