


DOWNLIGHT LIDER Z 940 23W 60° WHITE HI EFFICIENT ON/OFF

COB

4000 [K] HI EFFICIENT

Article number: N202-K0003-BB940-H5-G60-ZA02_600-S1-###





Dow	nliał	nt LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

	CBI	EFFICIENT	
		90	
	Led chip flux	3793 [lm]	
	Luminous flux	3413 [lm]	
	System power		
	Luminaire Efficiency	23 [W]	
	Beam angle	148 [lm/W]	
	Controller	60°	
		ON/OFF	
	MacAdam	3 SDCM	
UMINAIRE			
	Weight	1,17 [kg]	

L

Light colour

Weight	1,17 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl

Street: Ignatza Hakuby 18 41-914 Bytom, Polska