

DOWNLIGHT LIDER Z 957 21W 15° WHITE SPECIAL ON/OFF

Article number: N202-K0003-CC957-H5-G15-ZA02_550-S1-###





LED COB

Light colour 5700 [K] SPECIAL

CRI 9

 CRI
 90

 Led chip flux
 2788 [Im]

 Luminous flux
 2509 [Im]

 System power
 21 [W]

 Luminaire Efficiency
 119 [Im/W]

 Beam angle
 15°

 Controller
 ON/OFF

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 1,17 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska