


DOWNLIGHT LIDER Z 957 14W 38° WHITE SPECIAL ON/OFF

Article number: N202-K0003-CC957-H5-G38-ZA01_350-S1-###





COB

Light colour 5700 [K] SPECIAL

CRI

Led chip flux 1820 [lm] Luminous flux 1638 [lm] System power 14 [W] Luminaire Efficiency 117 [lm/W] Beam angle 38° Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 1,17 [kg] Protection rating IP , IK , class IP 20, IK 1, WHITE Luminaire colour Cover Plastic Operating voltage 220-240V 50-60Hz

Downlight LED

Suspended LED downlight. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Power cord - 300cm. Reflector beams available: 15°, 23° 38°, 34° and 60°. Maximum power is 31W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, honeycomb louver on inquiry , Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska